

IN THE SPECIFICATION

At page 8 line 6, line 12, and line 21 have reference number corrections.

The clamp 10 can be rotated on fork tube 140 or 142 as shown by arrows 50 to adjust the position of the split ring for the handlebar 20 to a desired position to support the handlebar 20. In order to rotate the clamp 10 the split ring 12 is loosened by turning bolt 34 until gap 14 is large enough to rotate the split ring 12 on fork tube 40. When split ring 11 is in the desired position bolt 34 is tightened until the split ring 12 grips the fork tube 40 140 such that clamp 10 is prevented from rotating in the directions shown by arrows 50. In a similar fashion handlebar 20 can be raised or lowered on column 22 to adjust the height of the handlebar 20 as shown by arrows 51 and to rotate the handlebar as shown by arrows 52 to adjust the position of the handlebar 20 to the desired position which will make it easier and more comfortable for the rider to operate the motorcycle. When the handlebar 20 is in position bolt 34 in split ring 11 is tightened to grip column 22 of handlebar 20. In this manner the handlebars 20 can be added to the motorcycle ~~440~~ 100 with out taking off the windscreen 156 or the cowl 152 since the clamp 10 is of small height and length and can be attached to the fork tube 140 or 142 without interfering with the cowl 152 or the windscreen 156. Similarly the handlebar 20 can be attached to the clamp 10 by swiveling the clamp into a position whereby the handlebar 20 can be inserted into the aperture 111 in split ring portion 11 and rotated as shown by arrows 52 and raised or lowered as shown by arrows 51 to the desired position, which can be extended out of the cowling as a sports bike or raised and rotated toward the rider inside the cowling 152 and windscreen 156 to provide a touring bike style handlebar position. The raising or lowering and rotating of the handlebars 20 can be

accomplished to fit the contours of the cowling 152 and windscreen 156 so there is no interference.

On page 9 second paragraph remove the second period at the end of the sentence.

With the handlebars 20 raised and rotated toward the handlebars 20 are in the touring bike position, which is more comfortable for the rider. -